

Amendments to the Claims:

This listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

What is claimed is:

1. (Original) A method of processing a message to determine a tag value from the message and from a key according to a message authentication code, the method comprising:

selecting one of a plurality of symbols, the plurality of symbols forming a codeword encoding a data item derived from the message, the codeword encoding the data item according to an error correcting code, wherein said key determines which one of said plurality of symbols is selected; and

determining the tag value to be the selected symbol.

2. (Original) A method according to claim 1, wherein the data item derived from the message consists of said message.

3. (Original) A method according to claim 1, further comprising determining said data item to be a hash value of a one-way hash function calculated from the message.

4. (Original) A method according to claim 1, wherein the key is short enough to be communicated via a user interaction.

5. (Original) A method according to claim 1, wherein the error correcting code is a Reed-Solomon code and wherein the tag value is determined by evaluating a Reed-Solomon encoding polynomial at a point determined by the key.

6. (Original) A method according to claim 1, wherein the tag value is an element in a finite field.

7. (Original) A method according to claim 1, further comprising communicating at least a contribution to the message from a sender to a receiver via a first communications channel; and communicating the tag value and/or the key from the sender to the receiver via a second communications channel different from the first communications channel.

8. (Original) A method according to claim 7, wherein the second communications channel includes a user interaction.

9. (Previously Presented) A communications device for communicating data messages, the communications device comprising:

processing means that is adapted to determine a tag value from a message and from a key according to a message authentication code, and wherein the processing means is further adapted to select one of a plurality of symbols, the plurality of symbols forming a codeword encoding a data item derived from the message, the codeword encoding the data item according to an error correcting code, wherein said key determines which one of said plurality of symbols is selected, and wherein the processing means is further adapted to determine the tag value to be the selected symbol.

10. (Currently Amended) A computer program product embodied on a computer readable medium loaded into a memory and executed by a processor to

~~determine a tag value from a message and from a key according to a message authentication code, the computer program product comprising:~~

~~instructions causing the processor to determine a tag value from a message and from a key according to a message authentication code, further comprising:~~

~~a first code segment instructions causing the processor to select one of a plurality of symbols, the plurality of symbols forming a codeword encoding a data item derived from the message, the codeword encoding the data item according to an error correcting code, wherein said key determines which one of said plurality of symbols is selected; and~~

~~a second code segment instructions causing the processor to determine the tag value to be the selected symbol.~~

11. (Currently Amended) A computer program product embodied on a computer readable medium loaded into a memory and executed by a processor to ~~communicate data messages, the computer program product comprising:~~

~~instructions to cause the processor to communicate data messages;~~

~~a first code segment instructions to cause the processor to determine a tag value from a message and from a key according to a message authentication code;~~

~~a second code segment instructions to cause the processor to select one of a plurality of symbols, the plurality of symbols forming a codeword encoding a data item derived from the message, the codeword encoding the data item according to an error correcting code, wherein said key determines which one of said plurality of symbols is selected; and~~

~~a third code segment instructions to cause the processor to determine the tag value to be the selected symbol.~~

12. (Original) A communications device for communicating data messages, the communications device comprising:

a processing unit that is adapted to determine a tag value from a message and from a key according to a message authentication code, and wherein the processing

unit is adapted to select one of a plurality of symbols, the plurality of symbols forming a codeword encoding a data item derived from the message, the codeword encoding the data item according to an error correcting code, wherein said key determines which one of said plurality of symbols is selected, and wherein the processing unit is adapted to determine the tag value to be the selected symbol.